

Feature Highlights

- √ 2U ATX Rackmount Computer Chassis
- √ Drive Bays for two open 5.25", two 3.5" and Two internal 3.5"
- √ Lockable front door for running security
- √ Three 8cm (42.5CFM) ball bearing cooling fans
- √ 280W/300W ATX power supply optional
- √ Ideal for Firewall, Compact Server and Control server
- √ May use sliding rail for easy mounting



Feature	Description
Construction	Top cover: SECC 1.0mm thick
	Bottom Frame: SECC 1.2mm thick
	Internal Components: SECC 1.2mm thick
	Front Panel: SECC 2.0mm thick
	"L" Shaped Plate: Aluminum 3.0mm thick (both side of the chassis)
Drive Bay	Open: Two 5.25" and Two 3.5"; Internal: Two 3.5"
Cooling System	Three 8cm (42.5 CFM) ball bearing cooling fans with front and 2-side ventilation holes
Control Panel	LED indicators for HDD and power; Switches for reset and power On/Off
	Drive bays are protected by a lockable front door
Slot	1XPCI and 1xPCI/ISA shared on a riser card
Physical Dimension	19"(W) x 3.5" (H) x 25.5" (D) (483m x 89mm x 647.7mm)
Physical Color	Black: TL-RACK 230BATX
Standard of Compliance	Design meets FCC Class A/CE standards

Ordering Guide	Model #	Item #	Description
	TL-RACK 230BATX	RM230BKBP2S1P+1	2U, 19" Black ATX Rackmount Chassis with Riser Card
	280W Power supply	RM230XPS280WX	280W power supply
	300W Power supply	RM230X300WPFC-1	300W power supply (Intel Pentium 4 ready)

