

Feature Highlights

- ✓ 1.5U rack mount Keyboard/Mouse, sun light readable LCD and 8-port KVM switch
- ✓ 15" TFT LCD with 1024x768 display quality and 1400cd/m² brightness
- ✓ 8KVM console ports with no software required can be daisy chain up to 8 levels (120 systems)
- ✓ 25° tilt up and down for viewing comfort



Feature	Description
LCD Panel	15.0" diagonal TFT sun light readable LCD display 16.7 million color panel
Resolutions	1024 (H) x 768 (V)
Back Light	4 pcs. of CCFTs (Cold Cathode Florescent tube)
Brightness	1400 cd/m ²
Contrast Ratio	300:1
Viewing Angle	140° (Horizontal) 120° (Vertical)
Frequency	48.36-60 KHz (H), 60-75 KHz (V)
Daisy Chain MAX level	8 levels
KVM Control Board	8-port with 8 sets of 3-in-1 cable
PC Selection	On Screen Display Manual, Hot Key, Push button
Safety Standard	FCC, CE
LCD MTBF	35,000 hours
Power Comsumption	36 W max
Weight	26.22 lbs
Environment Information	Operation: 0~50°C; Operation humidity: 0~80% non-condensing

Ordering Guide	Model #	Item #	Description
	TL-KLS 108HL	RMX-KLS108BK-HL	TL-KLS 108HL 1.5U KB/TB/15" SUN LIGHT READABLE LCD/8-PC W/CABLE SET